PILOT DEVICES	Version	0.0
	Adoption Date:	1 July 2016
	Application Date:	1 January 2017
	Tier	5
This document is subject to controlled issue and can be found here: http://www.euromr.org/technical-requirements		
*** Uncontrolled if downloaded or printed ***		

### 1. PRODUCT DESCRIPTION

### 1.a General description of the product

**Pilot devices** are devices which communicate between human operators and machines using the following control circuit devices and switching elements.

- manual control switches, e.g. push-buttons, rotary switches, joystick etc.;
- associated control circuit equipment, e.g. indicator lights, etc.

**Note1**: A control switch includes (a) switching element(s) and an actuating system.

**Note2:** A switching element may be a contact element or a semiconductor element

### 1.b Application limitations

- a) The rated voltage of pilot devices shall be up to 1000V a.c. (50/60 Hz) or 600V d.c. according to IEC60947-5-1;
- b) The following devices, which are not relating to human operation, are excluded from these technical requirements:
  - pilot switches, for example pressure switches, temperature sensitive switches(thermostats), programmers, etc.;
  - **electromagnetically operated control switches**, either time-delayed or instantaneous, for example contactor relays
  - **position switches**, for example control switches operated by part of a machine or mechanism.

**Note:** pilot switches are non-manual control switches actuated in response to specified conditions of an actuating quantity. (IEV 441-14-48)

PILOT DEVICES	Version	0.0
	Adoption Date:	1 July 2016
	Application Date:	1 January 2017
	Tier	5
This document is subject to controlled issue and can be found here: <a href="http://www.euromr.org/technical-requirements">http://www.euromr.org/technical-requirements</a>		
*** Uncontrolled if downloaded or printed ***		

#### 1.c Intended use

Pilot devices are used for marine applications, e.g. electric motor control gears, switchboards, distribution boards, control panels, etc.

### 1.d System context

See 1.c above.

### 2. DESIGN EVALUATION

### 2.a Engineering evaluation requirements

### 2.a i. Technical Requirements

- a) Pilot devices shall be complied with the requirements of IEC 60947-5-1;
- b) Emergency stop devices with mechanical latching function shall be complied with IEC60947-5-5;
- c) Type, ratings and characteristics of pilot devices for intended applications shall be evaluated;
- d) Dependency of external control power shall be evaluated.

### 2.a.ii. Technical documents to be submitted

**IMPORTANT:** The English Language shall be used for all submitted documents.

#### **Prior to tests:**

- a) Proposed test program and test schedule;
- Description of the test specimens and explanation of the selected test sample(s) providing evidence that the selected sample meets the most rigorous and demanding requirements;
- c) Product descriptions, data sheets, assembly drawings, dimension drawings etc. clearly identifying the product;
- d) Complete accreditation certificate of the Test laboratory (prior the first test only; changes in the scope of accreditation shall also be advised);
- e) Details of production sites;
- f) Product specification;
- g) Application, working area;

PILOT DEVICES	Version	0.0
	Adoption Date:	1 July 2016
	Application Date:	1 January 2017
	Tier	5
This document is subject to controlled issue and can be found here: http://www.euromr.org/technical-requirements		
*** Uncontrolled if downloaded or printed ***		

- h) Instructions on fitting, assembly and operation;
- QM-certificate according to ISO 9001.

### After completion of tests:

- j) The test report with an identification number shall contain all relevant data and test results including place and date of the tests, the names of the responsible personnel carrying out the test;
- k) Type references and serial numbers of the products tested;
- Test reports and test records shall be signed by the personnel members in charge
  of the test and are to be confirmed by the EU RO by signing and marking the test
  report.

### 2.b Type testing requirements

- a) The test laboratory shall be accredited according to ISO 17025 for relevant IEC standards (incl. IEC 60947-5-1 sub-clause 8) by either a National Accreditation Body under the MLA regime of ILAC or one of the certification bodies under the LOVAG or IECEE Mutual Recognition Agreement.;
- b) Type test shall be carried out in accordance with IEC 60947-5-1 sub-clause 8.1.2 and, IEC 60947-5-5 sub-clause 7 for the emergency stop device with mechanical latching function.
- c) Special tests shall be carried out in accordance with IEC 60947-5-1 sub-clause 8.1.5 and Annex C Special tests Durability tests;
- d) EMC tests shall be carried out for pilot devices incorporating electronic devices in accordance with IEC 60947-1 sub-clause 7.3. In addition, compass safe distance test shall be carried out in accordance with IEC60945 sub-clause 11.2 when the pilot devices are installed in the vicinity of the ship's standard or steering compasses.
- e) All tests shall be performed on the agreed test samples taken from the production line or from stocks†;
- f) Tests shall be carried out in the presence of the EU RO Surveyor. In cases where the tests are conducted at Nationally Accredited Laboratories, the presence of the EU RO surveyor may be omitted<sup>†</sup>.

PILOT DEVICES	Version	0.0
	Adoption Date:	1 July 2016
	Application Date:	1 January 2017
	Tier	5
This document is subject to controlled issue and can be found here: http://www.euromr.org/technical-requirements		
*** Uncontrolled if downloaded or printed ***		

<sup>†</sup> For further clarification of witnessing of tests and sampling the test specimen(s), refer to paragraphs 6, 7 and 8 of the EU RO "Design Evaluation Scheme" procedure (Appendix V of EU RO Framework Document for the Mutual Recognition of Type Approval found on <a href="http://www.euromr.org/Guidance%20for%20Mutual%20Recognition">http://www.euromr.org/Guidance%20for%20Mutual%20Recognition</a>)

### 3. PRODUCTION REQUIREMENTS

- a) Refer to EU RO "Product Quality Assurance (PQA)" procedure (Appendix VI of EU RO Framework Document for the Mutual Recognition of Type Approval);
- b) Routine test according to IEC 60947-5-1 sub-clause 8.1.3;
- c) Production certification according to ISO 9001 by accredited certification bodies;
- d) QM/QS audit (annual) shall be submitted to EU RO for review;
- e) Production of the equipment is limited to those facilities listed on the EU RO certificate;
- f) Changes to the product will void the EU RO certification. The EU RO shall be kept informed of all new version numbers including a description of change;
- g) The EU RO shall be granted access to all manufacturing and testing facilities, and to be provided with all the information necessary to perform its duties;
- h) General terms and conditions of the EU RO shall be observed.

### 4. MARKING REQUIREMENTS

Marking as required by IEC 60947-5-1 sub-clause 5.2.

### 5. TYPE APPROVAL CERTIFICATE CONTENT

The EU RO MR Type Approval Certificate shall contain the minimum information as defined in the "EU RO Framework Document for the Mutual Recognition of Type Approval" - see Appendix I of EU RO MR Type Approval Certificate Information.

The following information is specifically applicable to products relevant to this technical requirement and shall be included on the EU RO MR Type Approval Certificate:

a) Technical data according to IEC marking;

PILOT DEVICES	Version	0.0
	Adoption Date:	1 July 2016
	Application Date:	1 January 2017
	Tier	5
This document is subject to controlled issue and can be found here: http://www.euromr.org/technical-requirements		
*** Uncontrolled if downloaded or printed ***		

- b) Reference to approved technical documents;
- c) Application and limitations.

### 6. APPROVAL DATE AND REVISION NUMBER

Date	Revision	Comment	
2016-07-01	0.0	Accepted by EU RO MR Advisory Board	

### 7. BACKGROUND INFORMATION / REFERENCES

- a) EU RO Framework Document for the Mutual Recognition of Type Approval;
- b) IEV 441-14-48;
- c) IEC 60947-1;
- d) IEC 60947-5-1;
- e) IEC 60947-5-5;
- f) IEC 60721-3-6 (1987) + A2 (1996);
- g) ISO 9001;
- h) ISO 17025.

# 8. MAINTENANCE / CLARIFICATION OF TECHNICAL REQUIREMENTS

Anyone wishing to propose changes to this document or request clarification of technical issues should contact the EU RO MR Group Secretariat in the first instance: <a href="mailto:Secretariat@euromr.org">Secretariat@euromr.org</a>.

Review and approval of change requests shall follow the EU RO MR Maintenance Process detailed in the EU RO Framework Document for the Mutual Recognition of Type Approval: <a href="http://www.euromr.org/Guidance%20for%20Mutual%20Recognition">http://www.euromr.org/Guidance%20for%20Mutual%20Recognition</a>

- END -