

EU RO Mutual Recognition Technical Requirements

POSITION SWITCHES	Version	0.2
	Adoption Date:	1 January 2023
	Application Date:	1 July 2023
	Tier	7
This document is subject to controlled issue and can be found here: http://www.euomr.org/technical-requirements *** Uncontrolled if downloaded or printed ***		

1. PRODUCT DESCRIPTION	1
2. DESIGN EVALUATION.....	2
3. PRODUCTION REQUIREMENTS.....	8
4. MARKING REQUIREMENTS.....	8
5. TYPE APPROVAL CERTIFICATE CONTENT	8
6. APPROVAL DATE AND REVISION NUMBER.....	9
7. BACKGROUND INFORMATION / REFERENCES.....	9
8. MAINTENANCE & CLARIFICATION OF TECHNICAL REQUIREMENTS	10
9. LEGAL PROVISIONS / COPYRIGHT.....	10

1. PRODUCT DESCRIPTION

1.a General description of the product

Position switches and proximity switches suitable for marine use.

Definitions according to IEC 60947-5-1 and IEC 60947-5-2:

- Position switch: "a pilot switch the actuating system of which is operated by a moving part of the machine, when this part reaches a predetermined position";
- Proximity switch: "a position switch which is operated without mechanical contact with the moving part";

The output of a position/proximity switch is determined by the presence or absence of a designated object. This digital output could be represented by a switched-, voltage-, current-, resistance- or frequency signal.

Typical principles of operation for sensing includes, but are not limited to:

- mechanical, capacitive, inductive, ultrasonic, photoelectric.

1.b Application limitations†

- a) Explosion proof 'Ex' certification is not within the scope of these Technical Requirements for all switches.
- b) These Technical Requirements are applicable to position switches for control, safety or alarm device of plant or system on board with rated voltage in electric circuit not exceeding 1000 V a.c. or 600 V d.c. for positions switches, and not exceeding 250 V a.c. or 300 V d.c. for proximity switches, in line with the requirements of IEC 60947-5-1 and IEC 60947-5-2.;

EU RO Mutual Recognition Technical Requirements

POSITION SWITCHES	Version	0.2
	Adoption Date:	1 January 2023
	Application Date:	1 July 2023
	Tier	7
This document is subject to controlled issue and can be found here: http://www.euromr.org/technical-requirements *** Uncontrolled if downloaded or printed ***		

- c) These Technical Requirements are not intended for position or proximity sensors/transmitters that output position values other than presence or absence. E.g. distance;
- d) Not applicable for a mobile offshore drilling unit (MODU);
- e) Not applicable for fishing vessels.

†The EU MR type approved product is generally not used as a stand-alone product, but integrated as component in a sub-system or system. When a product is presented with an EU RO MR Type Approval Certificate for given application, its acceptability with regards to conditions defined in 1b, 1c and 1d of this Technical Requirement will be evaluated by the EU RO in charge of classing the ship or being in charge of the unit/system certification.

1.c Intended use

Intended for use in systems that provide control, monitoring and alarm functions subject to classification requirements.

1.d System context

Application of the control, monitoring and alarm systems are subject for approval of the individual EU RO classing the vessel.

2. DESIGN EVALUATION

2.a Engineering evaluation requirements

2.a i. Technical Requirements

All technical requirements shall fulfil IACS Unified Requirements E10, latest revision in use– Test Specification for Type Approval:

- a) Reliable operation shall be ensured at relative air humidity of 100 % (referred to at +55°C) under the following ambient temperatures:
 - 0°C to +55°C in enclosed spaces
 - +5°C to +70°C close to combustion engines, boilers and similar
 - -25°C to +45°C on open deck (-25°C to +55°C for electronic equipment)No damage to electrical and electronic parts shall be caused by temperature up to +70°C;
- b) Switches shall operate reliably at shocks having an acceleration of ± 5.0 g and at a frequency of 40 to 80 shocks per minute.

EU RO Mutual Recognition Technical Requirements

POSITION SWITCHES	Version	0.2
	Adoption Date:	1 January 2023
	Application Date:	1 July 2023
	Tier	7
<p>This document is subject to controlled issue and can be found here: http://www.euromr.org/technical-requirements *** Uncontrolled if downloaded or printed ***</p>		

- c) Reliable operation of electrical and electronic parts shall be ensured at vibrations having a frequency of 2 Hz to 100 Hz, namely, with shift amplitude of ± 1 mm where the vibration frequency is between 2 Hz and 13.2 Hz, and with an acceleration of ± 0.7 g where the vibration frequency is between 13.2 Hz and 100 Hz;
- d) Reliable operation of electrical and electronic position switches mounted upon vibration sources (engines (ICE), compressors, etc.) or installed in steering flats shall be ensured at vibration frequencies of 2 Hz to 100 Hz, namely, with a shift amplitude of ± 1.6 mm where the frequency is between 2 Hz and 25 Hz, and with an acceleration of ± 4.0 g where the frequency is between 25 Hz and 100 Hz; For more severe conditions which may exist, for example on exhaust manifolds of high-speed ICE, 40 Hz to 2000 Hz – acceleration ± 10.0 g at 600°C;
- e) Reliable operation of electrical and electronic position switches shall be ensured at long-term heel up to 22.5° and at motions of 22.5° with a period of 10 s;
- f) The protective enclosure of electrical and electronic position switches shall be chosen in accordance with IEC 60529;
- g) Switches to be installed in locations with specific operating conditions (high or low temperature, excessive mechanical loads, etc.) shall be designed and tested with regard to the conditions;
- h) Electrical and electronic position switches shall be made of materials resistant to marine environment or shall be reliably protected from its harmful effects;
- i) In general, IEC 60947 shall be observed. IEC 60947-5-1 for position switches (mechanically actuated), and IEC 60947-5-2 for proximity switches (non-mechanically actuated); Switches having electric or electronic parts shall operate reliably in case of deviation of the power source parameters listed in Table 1 from nominal values:

Table 1

Parameter	Deviation from nominal value		
	Long-term.	Short-term	
	%	%	Time, s
Voltage (A. C.)	+6...-10	± 20	1.5
Frequency	± 5	± 10	5
Voltage (D. C.)	± 10	5 10	Cyclic deviation Ripple

EU RO Mutual Recognition Technical Requirements

POSITION SWITCHES	Version	0.2
	Adoption Date:	1 January 2023
	Application Date:	1 July 2023
	Tier	7
This document is subject to controlled issue and can be found here: http://www.euomr.org/technical-requirements *** Uncontrolled if downloaded or printed ***		

- j) Switches having electrical and/or electronic parts and supplied from accumulator batteries shall operate reliably with the following voltage variations from the nominal value:
 - from +30 to -25 per cent for the equipment, which is not disconnected from the battery during battery charging;
 - from + 20 to -25 per cent for the equipment, which is disconnected from the battery during battery charging.
- k) Provision shall be made to ensure the electromagnetic compatibility of electrical and electronic parts of switches as specified IEC Publication 61000-4-2, IEC Publication 61000-4-3, IEC Publication 61000-4-4, IEC Publication 61000-4-5, IEC Publication 61000-4-6;
- l) Provision shall be made to prevent incorrect connection of plug-in-sockets to the switches' outputs;
- m) The devices shall be capable of being tested during normal operation;
- n) Replaceable components, which require adjustment, as well as check-up points (terminals, monitoring jacks) shall be so arranged that easy access is possible at any time;
- o) The minimum degree of protection, as applicable, shall be in accordance with the requirements set forth by the EU RO in charge of the vessel's classification, as a function of the intended location;
- p) In general, IEC 60947 shall be observed. IEC 60947-5-1 for position switches (mechanically actuated), and IEC 60947-5-2 for proximity switches (nonmechanically actuated)

2.a.ii. Technical documents to be submitted

Prior to tests:

- a) Technical data and specifications
- b) Dimensional/sectional views drawings
- c) Functional block diagrams of the article with indication of input and output signals, feedbacks, self-monitoring system, etc.;
- d) Product description including application, working area, working principle and operation
- e) Installation manuals
- f) Type test reports done previously if available
- g) Proposed test program and test schedule

EU RO Mutual Recognition Technical Requirements

POSITION SWITCHES	Version	0.2
	Adoption Date:	1 January 2023
	Application Date:	1 July 2023
	Tier	7
This document is subject to controlled issue and can be found here: http://www.euomr.org/technical-requirements *** Uncontrolled if downloaded or printed ***		

- h) Description of the test specimens and explanation of the selected test sample(s) providing evidence that the selected sample meets the most rigorous and demanding requirements;
- i) Details of the production site(s), production facility inspection report, production specifications and a valid QM certificate according to ISO 9001.
- j) Complete accreditation certificate of the Test laboratory (prior the first test only; changes in the scope of accreditation shall also be advised);
- k) For tests witnessed by the RO, the test report after completion of the testing shall contain:
 - an identification number;
 - all relevant data and test results including the place, date and names of personnel responsible for conducting the test;
 - type references and serial numbers of the products tested;
 - details of the test equipment used including the calibration certificates and serial numbers;Test reports shall be signed and dated by the person(s) responsible for conducting the test and by the attending EU RO witnessing the test.
- l) Test reports for tests performed at accredited test laboratories shall be in accordance with ISO/IEC 17025.

2.b Type testing requirements

- a) In general, the type test plan is to be agreed between the Manufacturer and the RO based on the characteristics of the product subject to testing.
- b) The type tests are intended to demonstrate the performance of the prototype according to the requirements of the applicable International Standards and the relevant Manufacturer's specification.
- c) The ability of the product to function as intended under the testing conditions specified in the latest revision of IACS UR E10 shall also be verified. Testing procedures according to the International Standards mentioned in this TR may be accepted by the RO, in lieu of those indicated in the IACS UR E10, provided that the test severity conditions set by the IACS UR E10 are fulfilled as a minimum.
- d) Performance type tests according to the Manufacturer's specification and the applicable International Standards shall be carried out.
- e) Visual inspection to check conformance to relevant drawings and design data shall be carried out.

EU RO Mutual Recognition Technical Requirements

POSITION SWITCHES	Version	0.2
	Adoption Date:	1 January 2023
	Application Date:	1 July 2023
	Tier	7
This document is subject to controlled issue and can be found here: http://www.euromr.org/technical-requirements *** Uncontrolled if downloaded or printed ***		

- f) Type tests shall be carried out in accordance with IACS UR E10. Additional tests and tests differing from the test specifications in IACS UR E10 shall be carried out as per Table 2. Tests for specific operating conditions to be carried out as relevant (increased temperatures, vibration levels, etc.);

Table 2:

No.	Test	Test parameters or reference to normative document	Test conditions	Test purpose, performance criteria	
1	Protective enclosure	IEC 60529	The test is applicable for enclosures of the articles with operating voltage up to 1000V.	The equipment is considered to have passed the test if it satisfies the Performance Criterion A and the requirements of IEC 60529.	
2	Impact	IEC 60068-2-27, Test Ea: - Acceleration: 5 g, - Duration: 10 ms – 15 ms, - No of impacts: 20 (10 per direction) - Frequency of impacts: 40 – 80 impacts/min	The test shall be carried out under working condition, in three mutually perpendicular planes. Sinusoidal shape of the impact momentum is recommended	The equipment is considered to have passed the test, if during and after the test it complies with the requirements specified in the technical documentation.	
3	Exposure to solar radiation	-Temperature in the chamber: + 55°C.	Subjected to the test are appliances with the use of plastics which are intended for operation on the open deck in areas where they are continuously exposed to solar radiation	The equipment is considered to have passed the test, if:	
		- Radiation intensity: 1125W/m ² .			- No deformation, cracking, stratification, buckling, ungluing of plastic pieces and other materials has taken place;
		(Including flux density of the ultra-violet portion			- No degradation of readability of inscriptions

EU RO Mutual Recognition Technical Requirements

POSITION SWITCHES	Version	0.2
	Adoption Date:	1 January 2023
	Application Date:	1 July 2023
	Tier	7
This document is subject to controlled issue and can be found here: http://www.euromr.org/technical-requirements *** Uncontrolled if downloaded or printed ***		

No.	Test	Test parameters or reference to normative document	Test conditions	Test purpose, performance criteria
		of spectrum with a wavelength of 280 – 400 nm shall be not less than 42 W/m ²)		and signs on the instrument scales has not been detected; -Parameters and resistance of insulation have remained normal
4	Inclination test	Limiting inclination angle 22,5°. Motions period 7...9 seconds.	Conditioning of equipment sequentially in two mutually perpendicular positions at an angle of 22,5° to the horizontal and measurement of parameters, but not less than 15 min in each position. Parameters shall be read at least 3 times in each position.	During and after the test, the switches shall be in good working order.
5	Cold test	As per UR E10 Cold test requirements except the duration. Duration is 16 hours.	As per UR E10 Cold test, but duration – 16 hours	As per UR E10

- g) Electromagnetic compatibility (EMC) to be tested in accordance with UR E10 (test item according to IEC 60533, and test parameters and performance criteria according to UR E10); or in accordance with IEC 60947-5-1 and IEC 60947-5-2 product standards (test parameters and performance criteria according to UR E10), plus additional test required by UR E10 (test item according to IEC 60533);
- h) All tests to be performed on agreed test samples.
- i) Test specimens shall be selected from the production line or at random from stocks †;

EU RO Mutual Recognition Technical Requirements

POSITION SWITCHES	Version	0.2
	Adoption Date:	1 January 2023
	Application Date:	1 July 2023
	Tier	7
This document is subject to controlled issue and can be found here: http://www.euomr.org/technical-requirements *** Uncontrolled if downloaded or printed ***		

- j) Tests shall be carried out in the presence of the EU RO Surveyor. In cases where the tests are conducted at a Nationally Accredited Laboratory, the presence of the EU RO's Surveyor may be omitted †.

† For further clarification of witnessing of tests and sampling the test specimen(s), refer to paragraph 6, 7 and 8 of the EU RO "Design Evaluation Scheme" procedure (Appendix V of EU RO Framework Document for the Mutual Recognition of Type Approval found on <https://www.euomr.org/technical-requirements>)

2.c Type testing requirement for certificate renewal

The manufacturer is to notify the RO of any modification or changes to the manufacturing specifications that may affect the MR TA to be renewed.

3. PRODUCTION REQUIREMENTS

Refer to EU RO "Product Quality Assurance (PQA)" procedure (Appendix VI of EU RO Framework Document for the Mutual Recognition of Type Approval); found on <https://www.euomr.org/technical-requirements>

4. MARKING REQUIREMENTS

Manufacturers of the approved equipment are, in principle, to mark the product before shipment for identification of approved equipment as per referenced standard. In addition, and as a minimum, the following items to be marked at the suitable place:

- a) Manufacturer's name or equivalent;
- b) Type No. or symbol;
- c) Serial No. and date of manufacture;
- d) Particulars or ratings
- e) IP ratings
- f) Operating temperature

5. TYPE APPROVAL CERTIFICATE CONTENT

The EU RO MR Type Approval Certificate shall contain the minimum information as defined in the "EU RO Framework Document for the Mutual Recognition of Type Approval" - see Appendix I EU RO MR Type Approval Certificate Information.

EU RO Mutual Recognition Technical Requirements

POSITION SWITCHES	Version	0.2
	Adoption Date:	1 January 2023
	Application Date:	1 July 2023
	Tier	7
This document is subject to controlled issue and can be found here: http://www.euomr.org/technical-requirements *** Uncontrolled if downloaded or printed ***		

The following information is specifically applicable to products relevant to this technical requirement and shall be included on the EU RO MR Type Approval Certificate:

- a) Environmental test items and test levels applied including IP rating, if any;
- b) Name and version/revision of hardware, firmware and software, as applicable;
- c) Approval conditions including limitations, if any;
- d) Intended use and system context;
- e) List of EMC test levels applied, as applicable;
- f) List of process media for which certification is granted, as applicable.
- g) Technical characteristic which adequately express the basic article's features assuring its functional usage;
- h) h) Other important characteristics specified by this Technical Requirement, including the power supply parameter

6. APPROVAL DATE AND REVISION NUMBER

Date	Revision	Comment
2019-07-01	0.0	Approved by EU RO MR Steering Committee
2021-03-01	0.1	Harmonised EMC testing requirements (18042h)
2022-06-30	0.2	Added para. 2c. Text alignment according to TG Grouping of TRs (20058) CRF055 Alignment of TRs by including the most rigorous requirement ((8 ± 1) s CRF056 Alignment of TRs by aligning reliable operations with a period of 10 s Added para 9 Copyright (ref 21030_)

7. BACKGROUND INFORMATION / REFERENCES

- a) EU RO Framework Document for the Mutual Recognition of Type Approval;
- b) IACS UR E10, latest revision in use – Test Specification for Type Approval;
- c) IEC 60529 Degrees of protection provided by enclosures (IP Code);
- d) IEC 60947-5-1 Low-voltage switchgear and control gear – Part 5-1: Control circuit devices and switching elements – Electromechanical control circuit devices;
- e) IEC 60947-5-2 Low-voltage switchgear and control gear – Part 5-2: Control circuit devices and switching elements – Proximity switches.
- f) IEC 60068-2-27

EU RO Mutual Recognition Technical Requirements

POSITION SWITCHES	Version	0.2
	Adoption Date:	1 January 2023
	Application Date:	1 July 2023
	Tier	7
This document is subject to controlled issue and can be found here: http://www.euomr.org/technical-requirements *** Uncontrolled if downloaded or printed ***		

8. MAINTENANCE & CLARIFICATION OF TECHNICAL REQUIREMENTS

Anyone wishing to propose changes to this document or request clarification of technical issues should contact the EU RO MR Group Secretariat in the first instance:

Secretariat@euomr.org.

Review and approval of change requests shall follow the EU RO MR Maintenance Process detailed in the EU RO Framework Document for the Mutual Recognition of Type Approval:

<https://www.euomr.org/technical-requirements>.

9. LEGAL PROVISIONS / COPYRIGHT

- a) Underlying legal provisions in accordance with EU RO Framework Document for the Mutual Recognition of Type Approval;
- b) Copyright © 2022. All EU RO MR Group rights reserved.
For a list of EU RO MR Group members please see <https://www.euomr.org/about-us>.

- END -